



## TIPPER BED TWIN WHEEL VERSION

The Tipper Bed version combines the strengths of the structure of the fixed deck with the **practicality of a tipper system with a maximum tip angle of 45°**. Ideal for **transporting and unloading loose and heavy materials**, this vehicle is the perfect answer to the needs of small construction businesses, for example.

PETROL + LPG



RANGE VARIANT	TWIN WHEEL VERSION				
	SHORT RANGE	LONG RANGE	SHORT RANGE	SHORT RANGE	LONG RANGE
WHEELBASE (mm)	3,000		3,250		
DIMENSIONS (l x w x h) (mm)	4,545 x 1,800 x 1,840		4,815 x 1,800 x 1,840	5,095 x 1,800 x 1,840	
LOAD BED DIM. (l x w) (mm)	2,530 x 1,800		2,800 x 1,800 <sup>(1)</sup>	3,080 x 1,800	
GVW (Kg)	2,520	2,800	2,520	2,520	2,800
EFFECTIVE LOAD CAPACITY (kg)	1,100	1,345	1,070	1,050	1,300

(1) Available with Short Range versions only

PETROL + METHANE



RANGE VARIANT	TWIN WHEEL VERSION				
	SHORT RANGE	LONG RANGE	SHORT RANGE	SHORT RANGE	LONG RANGE
WHEELBASE (mm)	3,000		3,250		
DIMENSIONS (l x w x h) (mm)	4,545 x 1,800 x 1,840		4,815 x 1,800 x 1,840	5,095 x 1,800 x 1,840	
LOAD BED DIM. (l x w) (mm)	2,530 x 1,800		2,800 x 1,800 <sup>(1)</sup>	3,080 x 1,800	
GVW (Kg)	2,520	2,800	2,520	2,520	2,800
EFFECTIVE LOAD CAPACITY (kg)	1,040	1,245	1,010	995	1,195

(1) Available with Short Range versions only